



- High Corrosion & Abrasion Resistance
- Increased Water Capacity
- Extended 6'6" Dumping Height
- WhisperWheel Fan Technology

- Large Separate Cleanout Door
- Ground Level Cleanout Door Lift
- All LED Lighting
- 68 HP Tier 4 Final Engine

800.879.7933 www.schwarze.com

SuperVac Gale Force





Blast to suction

lateral transfer

Left (Driver side)

formed channel

82 in (2083 mm)

10 in (254 mm)

10 in (254 mm)

2 x front: 1 x rear

Vertical steel digger

Direct-drive hydraulic

4 x bolt-on disposable

39 in (991 mm)

WhisperWheeltm

30 in (762 mm)

Radial pressure

Banded belt

backward incline

Hardox AR steel

Less than 1.5 grams

Bolt-in corded rubber

torque motor


Variable

side plates

4 x adjustable springs

Single piece A36 steel

Carbide on adjustable



*TYPICAL MEASUREMENTS SHOWN , EXACT DIMENSIONS DEPENDING ON OPTIONS AND TRUCK MANUFACTURER

GENERAL SPECIFICATIONS

Total empty weight Overall width Overall length Overall height Wheelbase Turning radius Sweeping width (Head only) Sweeping width (1 broom) Sweeping width (2 brooms)

10,480 lb (4753.64 kg) 85 in (2159 mm) 238 in (6045 mm) 99 in (2515 mm) 132.5 in (3365 mm) 20 ft curb to curb 82 in (2083 mm) 103 in (2617 mm) 124 in (3150 mm)

Yanmar diesel

4TNV98C-NYEM

202.5 cu in (3319 cm3)

Three-point automatic

68 hp (50.4 kw)

12 volt: 55 amp

with pre-cleaner

Full-flow spin-on

Bolt-in AB steel

Liquid cooled

2 element

AUXILIARY ENGINE

Model Horse power Displacement Coolina Alternator Safety shutdown Air filter

Oil filter **DEBRIS HOPPER** Volumetric Capacity

Dumpina Dump door Inspection doors Controls Dumpina heiaht Dump angle Dust separator

Construction

Intake tube

4.5 cu yd. (3.4 cu m) Stainless steel* (A36 carbon optional) Hvdraulic to the rear Twin cylinder hydraulic 1xper side (10in x 24in) In cab 77in 88 dearees Centrifugal

DUST CONTROL SYSTEM

Pump Capacity Tank construction

Filtration Nozzles

Optional tank

TOOL STORAGE

Location Capacity Latches Shovel rack

HYDRAULIC SYSTEM

Type Capacity Drive Filtration Hoses

CONTROL SYSTEM

Location Switches Labeling Throttle Vacuum enhancer

side broom 45 gal

Two at rear of sweeper 17.25 cu ft (0.489 m³) Lockable and adjustable 2 x 2 inch tubes side to side

Fixed-displacement

Heavy duty

Polvethylene

electric diaphraam

65 gal (Gas chassis)

Hopper; pickup head;

130 gal (Diesel chassis);

Cleanable 50 mesh filter

gear pump 15 aal (57 L) Direct mount to engine 10 micron element Rough-service double wire

Gauges

In cab Heavy-duty rocker International symbol

Electronic Electric actuator with indicator Tachometer; hour-meter; oil pressure; water temperature

SWEEPER WARRANTY

- 12 months / 1200 hours
- 60 month limited on hydraulics

PICKUP HEAD

Type Suction side Suspension Construction

Widt.h Suction diameter Blast diameter Skids

Rubber flaps

SIDE BROOM

Type Diameter Drive

Speed Seaments

FAN SYSTEM

Design Diameter Type

Drive Construction Balance Housing liner

CHASSIS (PRIMARY)

Make Model Type GVWR/GCWR

Engine

Transmission

Frame Tires Wheels

Brakes

Steering Electrical

Alternator **Batteries** Exhaust

charged 4HK1-TC 6 speed automatic with double overdrive 11.89 cu in section

Isuzu

NPR HD

modulus 215/85R-16E (10 plv)

6 hole steel disc Vacuum / hydraulic with 4 channel ABS Integral hydraulic

Cab-over engine (COE)

14,500 lb / 20,500 lb (5152 kg / 9298 kg) Diesel 215 hp turbo

with tilt & telescopic 12 volt 140 amp Dual 750 cca

Vertical

PAINT

Hopper Underbody DuPont Imron Flite Textured black urethane

SAFETY EQUIPMENT

- Hopper safety props
- 4 way LED flashing lights
- Dual rear facing strobes Rear view camera system
- Back-up alarm
- Optional: strobes: beacons: arrow boards

Note: design and specifications subject to change without notice

Schwarze parking lot sweepers are guaranteed to be free from defects due to faulty materials and / or workmanship for a period of 12 months, or 1200 hours. Liability is limited to replacement or repair of defective part(s) at factory or authorized dealer. The standard warranties of the chassis and auxiliary engine manufacturer shall apply.

Your Schwarze Representative

Affiliates:













Also Available from Schwarze Industries, Inc:



















© Schwarze Industries 2019 1055 Jordan Road Huntsville, AL 35811 800.879.7933 An Alamo-Group Company

