

HOT PRODUCTS

TRAILER



HOT PRODUCTS TRAILER

MAC LTT offers our customers an extensive line of Hot Products Semi Trailers, Trains and Truck Mount Tanks. With two strategically located manufacturing facilities, state of the art equipment and a vastly experienced Management, Engineering and Manufacturing staff, we are able to serve you from coast to coast.

MAC Liquid Tank Trailers are custom built to transport various hot products for your specific needs. Rest assured that when you go with MAC, our trailers endure a rigorous quality inspection to ensure endurance and safety!

- Wide variety of piping, heating and pumping options available
- Professional insulation and jacketing insulation installed for a clean flawless finish
- Aerodynamic options available, including but not limited to, internal vapor recovery systems, over turn protection wind dams, and under carriage trailer skirting.
- Various walk way configurations to ensure driver safety and user-friendly along with being ergonomically designed.
- Designed for user-friendliness and ergonomically safe operation and backed by MAC LTT parts, service, and warranty

2016 BASE MODEL ARJ-7500-1-HP Aluminum Insulated & Jacketed 7,500 Gallon One Compartment Asphalt Tank with Air Suspension

Overall Length/Shape	42 Foot Straight Round with 3" Slope to Rear
Capacity	7,500 Gallons +1%
Operating Temp.	375 F
Operating Pres.	Atmospheric
Insulation Jacketing	5" Fiberglass Compressed to 4" 0.040" Jacket Side Sheets / 0.080" Aluminum Heads, with Three (3) Center Sheets Pre-Painted Black
Thermometer	Install 0° F to 400° F 2" Dial in Well with Plexiglass Cover Near Center of Trailer on Curbside
Suspension	Hendrickson Intraxx AANT23K Air Suspension with HXL5 5 Year Warranty Package
Hangers/Brackets	Standard with Galvanized Hangers and Hanger Support Brackets
Suspension Track	71 1/2" Track
Suspension Spread	49" Axle Spacing
Subframe	38" Wide Aluminum Extruded Subframe Bolted to Aluminum Tank Frame
Hub/Drum	11.25 Bolt Circle x 10 Stud Hub-Piloted, Dura-Light Hub with Cast Drum
ABS/Roll Stability	ABS-Haldex 4S/2M without Roll Stability System or Equivalent
Wheels	Alcoa 24.5 X 8.25 Hub Piloted 10 Hole Aluminum Wheels with LVL Finish
Tires	11R-24.5 BF Goodrich ST230 Tires or Equivalent
Hose Carrier	3 1/2" Tall Approximately x 18" Wide x 21' Aluminum Hose Tray with Tarp Straps
Discharge Lines	4" Valve with 4" Line and 4" x 3" Thread on Adapter and Cap Extended Towards Rear
Sample Line	Install 3/4" Sampling Valve at Rear on Roadside
Pump Lines	3" Internal Pump Off Line from Front Curbside to Rear Discharge Valve with 3" Valve, Adapter, and Cap

These units come standard with:



4" BETT Asphalt Valve with 4" Outlet Connection




3 Disc Markers



Single Latch Manway – Easy Access Vent Box



3" Front Pump Off



MAC LTT IS COMMITTED TO QUALITY, CUSTOMER SERVICE AND PERFORMANCE
TO ENSURE THAT OUR VALUED CUSTOMERS GET THE PRODUCT THEY EXPECT AND
DESERVE – PRODUCT THAT PERFORMS TO THE STANDARDS THE CUSTOMER REQUESTS!



Experience Excellence

As a manufacturer, MAC LTT recognizes the complexity of today's ever changing market and the necessity to make you more competitive with advanced design trailers that will reduce weights, optimize payloads, maximize performance and enhance ergonomics to increase your overall profitability.

For MAC LTT, **new technology** is
not something you purchase, but rather
have the **vision and ability to create.**



1400 Fairchild, Ave.,
Kent, Ohio 44240
330-474-3795
330-968-4865 fax

1430 HWY 87 E
Billings, MT 59101
406-252-7163
406-256-6159 fax

855-6MACLTT
sales@macitt.com • www.macitt.com