

STUMP CUTTER

FEATURES AND BENEFITS

- 53.4-hp Kubota engine
- Radio remote controls
- Swing-out operator control station
- Can be operated from a handheld remote control or from swing out panel
- Retractable undercarriage (50-inch extended / 35-inch retracted)
- Non-marking rubber tracks
- Hydraulic backfill blade
- Two-speed ground travel
- Low center of gravity
- Slewing ring pivot design





General	US	Metric
Weight	3,360 lb	1,524 kg
Length	144"	366 cm
Height	73"	185 cm
Width	50" Expanded / 35" Retracted	127 cm / 89 cm
Chip Collection Capacity	11 cu ft	311 L
Tracks	Non-marking Rubber	
Engine	53.4-hp Kubota	40 kW Kubota
Fuel Type	Gasoline	Petrol
Fuel Tank Capacity	8.5 gallon	32 L
Hydraulic Oil Capacity	1.5 gallon	5.7 L
Cutting Wheel Diameter	20"	51 cm
Cutting Wheel Thickness	1.5"	4 cm
Cutter Teeth Quantity	24 Super Tooth®	
Cutting Depth	14"	36 cm
Cutting Height	24.5"	62 cm
Cutting Width	60"	152 cm



The expandable, non-marking rubber track undercarriage provides a stable, 50-inch wide, stance for cutting while retracting to 35-inches to squeeze through backyard gates.



The wide hydraulic backfill blade saves time during clean up and can easily be folded in for passing through gates.



The wireless remote control unit is sealed against dust, water, and other elements.

