

PP350-PP950

Compactor

engcon®

For all excavators between 13,200-72,600 lbs
(6-33 metric ton)



- » Easily adaptable for the EC-Oil automatic oil connector system and can thus be connected without the operator having to leave the cab
- » Compaction plate in hard-wearing steel
- » Side plating for leveling-off filler material
- » Open short ends to facilitate clearing the top of the plate
- » Joined with rubber elements located for effective insulation of the vibrators combined with adequate stiffness for grading
- » The vibrator unit and hydraulic parts are well-protected inside the side plates
- » Can be fitted with optional bracket
- » Complete with flow control valve
- » Complies with European safety standards
- » Supplied as standard excluding bracket and machine hoses
- » Tandem-connected weights



Specifications

Model	PP350	PP950
Compaction force (lbs):	7,720	20,940
Compaction area: (inch ²)	16.5	35.4
Max hydraulic pressure: (psi)	3,200	3,200
Rec hydraulic flow: (gal/min)	18	31.7
Max rec return hose pressure: (psi)	145	145
Weight excluding attachment point: (lbs)	860	1,980
Length: (inch)	35.04	50
Width: (inch)	24.41	35.43
Height: (inch)	17.72	23.62

NEWS! The EC-Oil automatic Quick Coupler system is a free standard on all engcon's hydraulic tools with S45-S80 attachment points.

CHANGE THE WORLD OF DIGGING

engcon North America Inc. | 2666 State Street, Hamden CT 06517
Phone +1 203 691 5920 | Email northamerica@engcon.com | Web engcon.com